

PRODUCT DATA SHEET

Kao Wall/Ceiling - Kit G



DESIGN BY:

Bruno Houssin

MATERIALS:

Painted Aluminium

DESCRIPTION:

Series of wall- or ceiling-mounting lighting structures with indirect lighting using 24W and 54W T16 fluorescent lamps, intended for the illumination of spaces such as entrance halls, reception areas, corridors, meeting rooms, etc. Aluminium body with white paint finish. 40x40mm square section modules. Distance to wall or ceiling: 16cm. Each structure is composed of pre-assembled and prewired sub-units, with a drilling stencil for placing the fixing points. Electrical connection via quick connectors. Electronic control gear. Dust protection cover in polycarbonate. Complies with standard EN60598-1 and other specific standards.

Light emission

Indirect



TECHNICAL DATA SHEET

Features

Product name: Kao Wall/Ceiling - Kit G

Article Code: M113220 Colour: White

Material: Painted Aluminium
Series: Architectural
Environment: Indoor

Area contract:

OPTICS

Emission: Indirect

DIMENSIONS

Length: (cm) 520 **Width:** (cm) 345

Cutout shape:


Weight: 25 Glow Wire Test: 850 °

LAMPS NOT INCLUDED

Category: FLUO Number: Lbs: T16 Watt: 24 Socket: G5 FDH-24 Type: Luminous Flux (Im): 1750 Colour Rendering: 85 Colour temperature (K): 3000 Duration (h): 20000

FLUO Category: Number: Lbs: T16 Watt: 54 Socket: G5 FDH-54 Type: 4450 Luminous Flux (Im): Colour Rendering: 85 Colour temperature (K): 3000 Duration (h):

Dimensions



LAMP



ELECTRICAL

Starter: Electronic Integrated Voltage: 220V-240V