

BEGA**33 384**

Wall luminaire



Project · Reference number



Date

Product data sheet

Application

Shielded LED wall luminaire with high protection class for a variety of lighting tasks. A luminaire made of die cast aluminium and impact resistant crystal glass.

Product description

Luminaire made of aluminium alloy, aluminium and stainless steel
 Crystal glass coated
 2 mounting holes \varnothing 4.5 mm
 Distance apart 210 mm
 2 cable entries for through-wiring of mains supply cable \varnothing 7-10,5 mm, max. 3G1.5[□]
 Connecting terminal 2.5[□]
 Earth conductor connection
 LED power supply unit
 220-240 V \sphericalangle 0/50-60 Hz
 DC 176-264 V
 Safety class I
 Protection class IP 65
 Dust-tight and protection against water jets
 Impact strength IK07
 Protection against mechanical impacts < 2 joule
 – Safety mark
 – Conformity mark
 Weight: 2.8 kg

Inrush current

Inrush current: 11 A / 112 μ s
 Maximum number of luminaires of this type per miniature circuit breaker:
 B 10A: 34 luminaires
 B 16A: 55 luminaires
 C 10A: 57 luminaires
 C 16A: 92 luminaires

Lamp

Module connected wattage	6.7 W
Luminaire connected wattage	7.8 W
Rated temperature	$t_a = 25^\circ\text{C}$
Ambient temperature	$t_{a\text{max}} = 50^\circ\text{C}$


On request we can offer you modifications for environments with higher temperatures as a customized product.

33 384 K3

Module designation	LED-0314/930
Colour temperature	3000 K
Colour rendering index	CRI > 90
Module luminous flux	1100 lm
Luminaire luminous flux	593 lm
Luminaire luminous efficiency	76 lm/W

33 384 K4

Module designation	LED-0314/940
Colour temperature	4000 K
Colour rendering index	CRI > 90
Module luminous flux	1135 lm
Luminaire luminous flux	612 lm
Luminaire luminous efficiency	78,5 lm/W



Lifetime of the LED

Ambient temperature $t_a = 15^\circ\text{C}$
 – at 50,000 h: L90B10
 – at > 500,000 h: L70B50
 Ambient temperature $t_a = 25^\circ\text{C}$
 – at 50,000 h: L90B10
 – at > 500,000 h: L70B50

max. ambient temperature $t_a = 50^\circ\text{C}$
 – at 50,000 h: L90B50
 – at 160,000 h: L70B50

Light technique

Luminaire data for the light planning program DIALux for outdoor lighting, street lighting and indoor lighting as well as luminaire data in EULUMDAT- and IES-format you will find on the BEGA web page www.bega.com.

Article No. 33 384

LED colour temperature optionally 3000 K or 4000 K
 3000 K – Article number + **K3**
 4000 K – Article number + **K4**

Colour graphite or silver
 graphite – article number
 silver – article number + **A**