



<b>Light source</b>	LED
<b>Work equipment</b>	Without
<b>Connected load</b>	16 - 32 V; DC
<b>Power consumption</b>	ca. 8,5 W
<b>Luminous flux</b>	approx. 940 lm
<b>Light type/-color</b>	Daylight
<b>Colour temperatur</b>	approx. 5.400 K
<b>Color rendering index</b>	CRI ≥ 80
<b>Light distribution</b>	Direct
<b>Direct ratio</b>	approx. 83 %
<b>Beam angle</b>	>120°
<b>Chromaticity tolerance LED</b>	< 5 SDCM
<b>Glare control</b>	Without
<b>Luminance (L65)</b>	≤ 4.000 cd/m <sup>2</sup>
<b>Unified glare rating (4H 8H)</b>	≤ 22
<b>System of protection</b>	IP 67
<b>Class of protection</b>	III
<b>Technology</b>	Switchable; -
<b>Operation</b>	External
<b>Housing</b>	Polycarbonate (PC), opal white
<b>Light source cover</b>	Polycarbonate (PC)
<b>Weight (net)</b>	ca. 1,5 kg
<b>Mains lead</b>	Built-in plug; QUICKON 3
<b>Fastening</b>	Lamp bracket (accessory)
<b>Dimension</b>	A=935 mm D=824 mm
<b>Light output</b>	A with plug
<b>Side part</b>	A with plug
<b>Minimum ambient temperature</b>	-25 °C
<b>Maximum ambient temperature</b>	40 °C
<b>Special features</b>	Through-wired

