



|                                     |                                |
|-------------------------------------|--------------------------------|
| <b>Light source</b>                 | LED                            |
| <b>Work equipment</b>               | Without                        |
| <b>Connected load</b>               | 16 - 32 V; DC                  |
| <b>Power consumption</b>            | ca. 10 W                       |
| <b>Luminous flux</b>                | approx. 950 lm                 |
| <b>Light type/-color</b>            | Daylight                       |
| <b>Colour temperatur</b>            | approx. 5.400 K                |
| <b>Color rendering index</b>        | CRI ≥ 80                       |
| <b>Light distribution</b>           | Direct                         |
| <b>Direct ratio</b>                 | approx. 82 %                   |
| <b>Beam angle</b>                   | >120°                          |
| <b>Chromaticity tolerance LED</b>   | < 5 SDCM                       |
| <b>Glare control</b>                | Without                        |
| <b>Luminance (L65)</b>              | ≤ 8.000 cd/m <sup>2</sup>      |
| <b>Unified glare rating (4H 8H)</b> | ≤ 25                           |
| <b>System of protection</b>         | IP 67                          |
| <b>Class of protection</b>          | III                            |
| <b>Technology</b>                   | Switchable; -                  |
| <b>Operation</b>                    | External                       |
| <b>Housing</b>                      | Polycarbonate (PC), opal white |
| <b>Light source cover</b>           | Polycarbonate (PC)             |
| <b>Weight (net)</b>                 | ca. 0,9 kg                     |
| <b>Mains lead</b>                   | Built-in plug; QUICKON 3       |
| <b>Fastening</b>                    | Lamp bracket (accessory)       |
| <b>Dimension</b>                    | A=652 mm                       |
| <b>Light output</b>                 | D=591 mm                       |
| <b>Side part</b>                    | D with plug                    |
| <b>Minimum ambient temperature</b>  | -25 °C                         |
| <b>Maximum ambient temperature</b>  | 40 °C                          |

