



| | |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Light source | LED |
| Work equipment | Adjustable electronic ballast, digital DALI |
| Connected load | 220 - 240 V; 50 Hz; 60 Hz |
| Power consumption | ca. 17 W |
| Standby | ca. 0,2 W |
| Power factor | env. 0,97 |
| Luminous flux | approx. 2.350 lm |
| Light type/-color | Cold white |
| Colour temperatur | approx. 4.000 K |
| Color rendering index | CRI ≥ 80 |
| Light distribution | Direct/indirect |
| Direct ratio | approx. 40 % |
| Chromaticity tolerance LED | < 3 SDCM |
| Glare control | Conical prismatic screen |
| Luminance (L65) | ≤ 2.700 cd/m ² |
| Unified glare rating (4H 8H) | ≤ 16 |
| System of protection | IP 40 |
| Technology | Continuously dimmable |
| Operation | External |
| Housing | Sectional aluminium; Silver |
| Light source cover | Acrylic (PMMA); Clear |
| Dimming Range | 1-100% |
| Weight (net) | ca. 3,3 kg |
| Mains lead | ca. 2 m; With free stranded wires |
| Fastening | Steel cable 0.3 - 0.7 m |
| Configuration | Start luminaire |
| Dimension | L=848mm |
| Life expectancy LED | L90B50 50.000h |
| Special features | Flicker-free; Start luminaire with mains connection; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch |