



<b>Light source</b>	LED
<b>Work equipment</b>	Adjustable electronic ballast, digital DALI
<b>Connected load</b>	220 - 240 V; 50 Hz; 60 Hz
<b>Power consumption</b>	ca. 17 W
<b>Standby</b>	ca. 0,2 W
<b>Power factor</b>	env. 0,97
<b>Luminous flux</b>	approx. 2.250 lm
<b>Light type/-color</b>	Warm white
<b>Colour temperatur</b>	approx. 3.000 K
<b>Color rendering index</b>	CRI ≥ 80
<b>Light distribution</b>	Direct/indirect
<b>Direct ratio</b>	approx. 40 %
<b>Chromaticity tolerance LED</b>	< 3 SDCM
<b>Glare control</b>	Conical prismatic screen
<b>Luminance (L65)</b>	≤ 2.700 cd/m <sup>2</sup>
<b>Unified glare rating (4H 8H)</b>	≤ 16
<b>System of protection</b>	IP 40
<b>Technology</b>	Continuously dimmable
<b>Operation</b>	External
<b>Housing</b>	Sectional aluminium; Silver
<b>Light source cover</b>	Acrylic (PMMA); Clear
<b>Dimming Range</b>	1-100%
<b>Weight (net)</b>	ca. 3,3 kg
<b>Mains lead</b>	ca. 2 m; With free stranded wires
<b>Fastening</b>	Steel cable 0.3 - 0.7 m
<b>Configuration</b>	Start luminaire
<b>Dimension</b>	L=848mm
<b>Life expectancy LED</b>	L90B50 50.000h
<b>Special features</b>	Flicker-free; Start luminaire with mains connection; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch