



Light source	LED
Work equipment	Adjustable electronic ballast, digital DALI
Connected load	220 - 240 V; 50 Hz; 60 Hz
Power consumption	ca. 46 W
Standby	ca. 0,15 W
Power factor	env. 0,980
Luminous flux	approx. 6.000 lm
Light type/-color	Warm white
Colour temperatur	approx. 3.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Direct ratio	approx. 40 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Conical prismatic screen
Luminance (L65)	≤ 2.700 cd/m ²
Unified glare rating (4H 8H)	≤ 16
System of protection	IP 40
Technology	Continuously dimmable
Operation	External
Housing	Sectional aluminium; Silver
Light source cover	Acrylic (PMMA); Clear
Dimming Range	1-100%
Weight (net)	ca. 7,5 kg
Mains lead	ca. 2 m; With free stranded wires
Fastening	Steel cable 0.3 - 0.7 m
Configuration	Start luminaire
Dimension	L=2250mm
Life expectancy LED	L90B50 50.000h
Special features	Flicker-free; Start luminaire with mains connection; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch