

**Light source****Work equipment****Connected load****Power consumption****Standby****Power factor****Luminous flux****Light type/-color****Colour temperatur****Color rendering index****Light distribution****Direct ratio****Chromaticity tolerance LED****Glare control****Luminance (L65)****Unified glare rating (4H 8H)****System of protection****Technology****Operation****Housing****Light source cover****Weight (net)****Mains lead****Fastening****Dimension****Life expectancy LED****Special features**

LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 9,5 W

ca. 0,2 W

env. 0,970

approx. 1.000 lm

Cold white

approx. 4.000 K

CRI \geq 80

Direct

approx. 100 %

< 3 SDCM

Conical prismatic screen

 \leq 3.000 cd/m² \leq 19

IP 40

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

ca. 3,1 kg

ca. 2 m; With free stranded wires

Steel cable 0.3 - 0.7 m

L=848mm

L90B50 50.000h

Flicker-free; Start luminaire with mains connection;
 DALI Load 1x; Suitable as emergency lighting;
 Through-wired, up to 18 m on one mains
 connection; Mechanical and electrical connection
 of the individual modules without tools; TouchDIM
 - dimming via standard switch