



Light source

Work equipment

Connected load

Power consumption

Standby

Power factor

Luminous flux

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Direct ratio

Chromaticity tolerance LED

Glare control

Luminance (L65)

System of protection

Technology

Operation

Housing

Light source cover

Weight (net)

Mains lead

Fastening

Dimension

Life expectancy LED

Special features

LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 16 W

ca. 0,15 W

env. 0,98

approx. 1.700 lm

Cold white

approx. 4.000 K

CRI \geq 80

Direct

approx. 100 %

< 3 SDCM

Conical prismatic screen

\leq 3.000 cd/m²

IP 40

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

ca. 4,7 kg

ca. 2 m; With free stranded wires

Steel cable 0.3 - 0.7 m

L=1408mm

L90B50 50.000h

Flicker-free; Start luminaire with mains connection;
DALI Load 1x; Suitable as emergency lighting;
Through-wired, up to 18 m on one mains
connection; Mechanical and electrical connection
of the individual modules without tools; TouchDIM
- dimming via standard switch