



**Light source**

**Work equipment**

**Connected load**

**Power consumption**

**Standby**

**Power factor**

**Luminous flux**

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Direct ratio**

**Chromaticity tolerance LED**

**Glare control**

**Luminance (L65)**

**System of protection**

**Technology**

**Operation**

**Housing**

**Light source cover**

**Weight (net)**

**Mains lead**

**Fastening**

**Dimension**

**Life expectancy LED**

**Special features**

LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 10 W

ca. 0,2 W

env. 0,970

approx. 1.000 lm

Warm white

approx. 3.000 K

CRI  $\geq$  80

Direct

approx. 100 %

< 3 SDCM

Conical prismatic screen

$\leq$  3.000 cd/m<sup>2</sup>

IP 40

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

ca. 3 kg

With free stranded wires

Steel cable 0.3 - 0.7 m

L=848mm

L90B50 50.000h

Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch