



**Light source**

**Work equipment**

**Connected load**

**Power consumption**

**Standby**

**Power factor**

**Luminous flux**

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Direct ratio**

**Chromaticity tolerance LED**

**Glare control**

**Luminance (L65)**

**Unified glare rating (4H 8H)**

**System of protection**

**Technology**

**Operation**

**Housing**

**Light source cover**

**Weight (net)**

**Mains lead**

**Fastening**

**Dimension**

**Life expectancy LED**

**Special features**

LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 13 W

ca. 0,2 W

env. 0,970

approx. 1.350 lm

Cold white

approx. 4.000 K

CRI  $\geq$  80

Direct

approx. 100 %

< 3 SDCM

Conical prismatic screen

$\leq$  3.000 cd/m<sup>2</sup>

$\leq$  19

IP 40

Continuously dimmable

External

Sectional aluminium; Silver

Acrylic (PMMA); Clear

ca. 3,9 kg

ca. 2 m; With free stranded wires

Steel cable 0.3 - 0.7 m

L=1128mm

L90B50 50.000h

Flicker-free; Start luminaire with mains connection;  
DALI Load 1x; Suitable as emergency lighting;  
Through-wired, up to 18 m on one mains  
connection; Mechanical and electrical connection  
of the individual modules without tools; TouchDIM  
- dimming via standard switch