


Free-standing luminaire YARA.single YAS 15000/840/RX/WS/CEE/S0/C

114268000-00807978


Waldmann **W**

ENGINEERS OF LIGHT



CEE 7/VII

D43 ↓ 13.0% ↑ 87.0%



Light source	LED
Work equipment	Electronic ballast DALI
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 107 W; 107 W
Power factor	env. 0,966
Luminous flux	approx. 15.000 lm
Luminous efficiency	approx. 140 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Direct ratio	approx. 13 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Conical prismatic screen
Luminance (L65)	≤ 2.700 cd/m ²
System of protection	IP 20
Class of protection	I
Technology	Multiple daylight-dependent motion sensors; DALI; Touch DIM; Wireless switch
Operation	
Housing	Aluminium/plastic; Powder coatet; White
Light source cover	Acrylic (PMMA); Structured; Satine
Arm	Steel tube; Powder-coated; Tubular section upright; White; C-form flat
Luminaire base	
Weight (net)	ca. 18 kg
Mains lead	ca. 3 m; Mains plug; CEE 7/VII
Fastening	Floor standing base
Life expectancy LED	L80B50 60.000h
Special features	Asymmetric radiation; Flicker-free; App control; Optional LTX Cloud connection; Direct and indirect lighting component with edge light and light guide technology for a homogeneous light exit; LTX multisensor for workplace optimisation; TALK Bluetooth; Magnetic control panel, freely positionable