



Light source	LED
Work equipment	Electronic ballast
Connected load	220 - 240 V; 50 Hz; 60 Hz
Power consumption	ca. 32 W
Standby	ca. 0,25 W
Power factor	env. 0,970
Luminous flux	approx. 3.150 lm
Light type/-color	Cold white
Colour temperatur	approx. 2.700 - 6.500 K
Color rendering index	CRI ≥ 90
Light distribution	Direct/indirect
Direct ratio	approx. 40 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Conical prismatic screen
Luminance (L65)	≤ 2.700 cd/m ²
Unified glare rating (4H 8H)	≤ 16
System of protection	IP 40
Technology	Continuously dimmable
Operation	External
Housing	Sectional aluminium; White
Light source cover	Acrylic (PMMA); Clear
Dimming Range	3-100%
Weight (net)	ca. 4,2 kg
Mains lead	ca. 2 m; With free stranded wires
Fastening	Steel cable 0.3 - 0.7 m
Configuration	Single Luminaire
Dimension	L=1134mm
Life expectancy LED	L90B50 50.000h
Special features	Flicker-free; DALI Load 1x; Suitable as emergency lighting; External control required for Dali Device type 8; Constant colour temperature over the whole dimming range; Constant luminous flux between 2700 and 6500 K; Specified values at approx. 4000 K