



| | |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Light source | LED |
| Work equipment | Electronic ballast |
| Connected load | 220 - 240 V; 50 Hz; 60 Hz |
| Power consumption | ca. 39 W |
| Standby | ca. 0,25 W |
| Power factor | env. 0,970 |
| Luminous flux | approx. 3.850 lm |
| Light type/-color | Cold white |
| Colour temperatur | approx. 2.700 - 6.500 K |
| Color rendering index | CRI ≥ 90 |
| Light distribution | Direct/indirect |
| Direct ratio | approx. 40 % |
| Chromaticity tolerance LED | < 3 SDCM |
| Glare control | Conical prismatic screen |
| Luminance (L65) | ≤ 2.700 cd/m ² |
| Unified glare rating (4H 8H) | ≤ 16 |
| System of protection | IP 40 |
| Technology | Continuously dimmable |
| Operation | External |
| Housing | Sectional aluminium; Silver |
| Light source cover | Acrylic (PMMA); Clear |
| Dimming Range | 3-100% |
| Weight (net) | ca. 5,1 kg |
| Mains lead | With free stranded wires |
| Fastening | Steel cable 0.3 - 0.7 m |
| Configuration | End luminaire |
| Dimension | L=1408mm |
| Life expectancy LED | L90B50 50.000h |
| Special features | Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; External control required for Dali Device type 8; Constant colour temperature over the whole dimming range; Constant luminous flux between 2700 and 6500 K; Specified values at approx. 4000 K |