



Light source	LED
Work equipment	Adjustable electronic ballast, digital DALI
Connected load	220 - 240 V; 50 Hz; 60 Hz
Power consumption	ca. 13 W
Standby	ca. 0,2 W
Power factor	env. 0,97
Luminous flux	approx. 1.350 lm
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct
Direct ratio	approx. 100 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Conical prismatic screen
Luminance (L65)	≤ 3.000 cd/m ²
Unified glare rating (4H 8H)	≤ 19
System of protection	IP 40
Class of protection	I
Technology	Continuously dimmable
Operation	External
Housing	Sectional aluminium; White
Light source cover	Acrylic (PMMA); Clear
Weight (net)	ca. 3,8 kg
Mains lead	Connector
Design	mounted version
Fastening	Ceiling mounted
Configuration	End luminaire
Dimension	L=1128mm
Life expectancy LED	L90B50 50.000h
Special features	Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch