



H	Φ : 4100 lm	E 0°	D
0.50 m	9450 lx	0.78 m 0.81 m	
1.00 m	2362 lx	1.55 m 1.61 m	
1.50 m	1050 lx	2.33 m 2.42 m	
2.00 m	591 lx	3.11 m 3.22 m	
2.50 m	378 lx	3.88 m 4.03 m	
3.00 m	262 lx	4.66 m 4.84 m	
3.50 m	193 lx	5.43 m 5.64 m	

Work equipment

Connected load

Power consumption

Standby

Power factor

Luminous flux

Luminous efficiency

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Direct ratio

Beam angle

Chromaticity tolerance LED

Glare control

Luminance (L65)

Unified glare rating (4H 8H)

System of protection

Class of protection

Technology

Operation

Housing

Weight (net)

Mains lead

Design

Installation dimensions

Life expectancy LED

Special features

Electronic ballast

220 - 240 V; 50 Hz; 60 Hz

ca. 30 W

ca. 0,5 W

env. 0,900

approx. 4.100 lm

approx. 136 lm/W

Cold white

approx. 4.000 K

CRI \geq 80

Direct

approx. 100 %

76° / 78°

< 3 SDCM

Conical prismatic screen

\leq 2.700 cd/m²

\leq 19

IP 20

II

Continuously dimmable

External

Sectional aluminium; White

ca. 3,1 kg

ca. 0,5 m; Connector

Integrated version

ca. 625 mm; 625 mm

L80B50 75.000h

Flicker-free; Direct light component with edge light and light-guide technology for homogenous light exit; DALI Load 1x; System dimension 625 x 625 mm; TouchDIM - dimming via standard switch; Strain relief with the possibility of through-wiring