



Height (m)	Beam diameter (m)	Beam diameter (m)	Illuminance (lx)
0.50 m	0.93 m	0.95 m	3719 lx
1.00 m	1.85 m	1.90 m	930 lx
1.50 m	2.78 m	2.86 m	413 lx
2.00 m	3.70 m	3.81 m	232 lx
2.50 m	4.63 m	4.76 m	149 lx
3.00 m	5.56 m	5.71 m	103 lx
3.50 m	6.48 m	6.67 m	75.9 lx

- Work equipment**
- Connected load**
- Power consumption**
- Standby**
- Power factor**
- Luminous flux**
- Luminous efficiency**
- Light type/-color**
- Colour temperatur**
- Color rendering index**
- Light distribution**
- Direct ratio**
- Beam angle**
- Chromaticity tolerance LED**
- Glare control**
- Luminance (L65)**
- Unified glare rating (4H 8H)**
- System of protection**
- Class of protection**
- Technology**
- Operation**
- Housing**
- Light source cover**
- Weight (net)**
- Mains lead**
- Design**
- Fastening**
- Dimension**
- Life expectancy LED**
- Special features**

- Adjustable electronic ballast, digital DALI
- 220 - 240 V; 50 Hz; 60 Hz
- ca. 16 W
- ca. 0,2 W
- env. 0,97
- approx. 1.700 lm
- approx. 106 lm/W
- Cold white
- approx. 4.000 K
- CRI ≥ 80
- Direct
- approx. 100 %
- 86
- < 3 SDCM
- Conical prismatic screen
- ≤ 3.000 cd/m²
- ≤ 19
- IP 40
- I
- Continuously dimmable
- External
- Sectional aluminium; White
- Acrylic (PMMA); Clear
- ca. 4,7 kg
- Connector
- Integrated version
- Fastening bow
- L=1414mm
- L90B50 50.000h
- Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch