



0.50 m	2844 lx	0.93 m 0.95 m
1.00 m	711 lx	1.85 m 1.90 m
1.50 m	316 lx	2.78 m 2.86 m
2.00 m	178 lx	3.70 m 3.81 m
2.50 m	114 lx	4.63 m 4.76 m
3.00 m	79.0 lx	5.56 m 5.71 m
3.50 m	58.0 lx	6.48 m 6.67 m

Work equipment

Connected load

Power consumption

Standby

Power factor

Luminous flux

Luminous efficiency

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Direct ratio

Beam angle

Chromaticity tolerance LED

Glare control

Luminance (L65)

Unified glare rating (4H 8H)

System of protection

Class of protection

Technology

Operation

Housing

Light source cover

Weight (net)

Mains lead

Design

Fastening

Dimension

Life expectancy LED

Special features

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 13 W

ca. 0,2 W

env. 0,97

approx. 1.300 lm

approx. 100 lm/W

Warm white

approx. 3.000 K

CRI ≥ 80

Direct

approx. 100 %

86

< 3 SDCM

Conical prismatic screen

≤ 3.000 cd/m²

≤ 19

IP 40

I

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

ca. 3,9 kg

Connector

Integrated version

Fastening bow

L=1134mm

L90B50 50.000h

Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch