



H	Φ : 1650 lm	E 0°	D
0.50 m	CO-C180: 86°	3610 lx	C90-C270: 87° 0.93 m 0.95 m
1.00 m		903 lx	1.85 m 1.90 m
1.50 m		401 lx	2.78 m 2.86 m
2.00 m		226 lx	3.70 m 3.81 m
2.50 m		144 lx	4.63 m 4.76 m
3.00 m		100 lx	5.56 m 5.71 m
3.50 m		73.7 lx	6.48 m 6.67 m

Work equipment

Connected load

Power consumption

Standby

Power factor

Luminous flux

Luminous efficiency

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Direct ratio

Beam angle

Chromaticity tolerance LED

Glare control

Luminance (L65)

Unified glare rating (4H 8H)

System of protection

Class of protection

Technology

Operation

Housing

Light source cover

Weight (net)

Mains lead

Design

Fastening

Dimension

Life expectancy LED

Special features

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 16 W

ca. 0,2 W

env. 0,97

approx. 1.650 lm

approx. 103 lm/W

Warm white

approx. 3.000 K

CRI \geq 80

Direct

approx. 100 %

86

< 3 SDCM

Conical prismatic screen

\leq 3.000 cd/m²

\leq 19

IP 40

I

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

ca. 4,7 kg

Connector

Integrated version

Fastening bow

L=1414mm

L90B50 50.000h

Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch