



H	$\Phi$ : 2650 lm	E 0°	D
0.50 m	5798 lx	0.93 m   0.95 m	
1.00 m	1450 lx	1.85 m   1.90 m	
1.50 m	644 lx	2.78 m   2.86 m	
2.00 m	362 lx	3.70 m   3.81 m	
2.50 m	232 lx	4.63 m   4.76 m	
3.00 m	161 lx	5.56 m   5.71 m	
3.50 m	118 lx	6.48 m   6.67 m	

**Work equipment**

**Connected load**

**Power consumption**

**Standby**

**Power factor**

**Luminous flux**

**Luminous efficiency**

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Direct ratio**

**Beam angle**

**Chromaticity tolerance LED**

**Glare control**

**Luminance (L65)**

**Unified glare rating (4H 8H)**

**System of protection**

**Class of protection**

**Technology**

**Operation**

**Housing**

**Light source cover**

**Weight (net)**

**Mains lead**

**Design**

**Fastening**

**Dimension**

**Life expectancy LED**

**Special features**

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 26 W

ca. 0,2 W

env. 0,97

approx. 2.650 lm

approx. 101 lm/W

Warm white

approx. 3.000 K

CRI  $\geq$  80

Direct

approx. 100 %

86

< 3 SDCM

Conical prismatic screen

$\leq$  3.000 cd/m<sup>2</sup>

$\leq$  19

IP 40

I

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

ca. 7,3 kg

Connector

Integrated version

Fastening bow

L=2256mm

L90B50 50.000h

Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch