



| | |
|---------------------------------------|--|
| Work equipment | Power supply unit |
| Connected load | 220 - 240 V; AC; 50 Hz; 60 Hz |
| Power consumption | ca. 71 W |
| Luminous flux | approx. 7.500 lm |
| Luminous efficiency | approx. 105 lm/W |
| Light type/-color | Warm white |
| Colour temperatur | approx. 3.000 K |
| Color rendering index | CRI ≥ 80 |
| Light distribution | Direct/indirect |
| Direct ratio | approx. 28 % |
| Chromaticity tolerance LED | < 3 SDCM |
| Glare control | See luminaire type |
| Unified glare rating (4H 8H) | ≤ 16 |
| System of protection | IP 20 |
| Class of protection | I |
| Technology | Two-stage switchable; - |
| Operation | External |
| Housing | Sectional aluminium; Anodised; Aluminium coloured anodised |
| Light source cover | Acrylic (PMMA); White opal |
| Weight (net) | ca. 4 kg |
| Mains lead | Connection box; 3 pin |
| Design | mounted version |
| Fastening | Mounting rail |
| Minimum ambient temperature | 25 °C |
| Decorative contrast side parts | White |
| Special features | General light; indirect; 3000K; Ra≥80; Reading light; direct; 3000K; Ra≥80; Protective low voltage relay (LVC) |