


Wall-mounted luminaire ZERA
ZEW 9000/830

114493000-00812996

Waldmann **W**


ENGINEERS OF LIGHT



CE UK

5 pin

D43 | 31.5% | 68.5% Φ: 7600 lm



Work equipment	Power supply unit
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 89 W
Luminous flux	approx. 8.960 lm
Luminous efficiency	approx. 100 lm/W
Light type/-color	Warm white
Colour temperatur	approx. 3.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Chromaticity tolerance LED	< 3 SDCM
Glare control	See luminaire type
System of protection	IP 20
Class of protection	I
Technology	Switchable
Operation	Switch
Housing	Sectional aluminium; Anodised; Aluminium coloured anodised
Light source cover	Acrylic (PMMA); White opal
Weight (net)	ca. 6,9 kg
Mains lead	Connector; 5 pin
Design	mounted version
Fastening	Wall bracket
Maximum ambient temperature	25 °C
Special features	General light; indirect; 3000K; Ra≥80; Night light; indirect; 3000K; Ra≥90; Reading light; direct; 2700K; Ra≥90; Examination light; direct; 4000K; 36W; Ra≥95; R9≥50; Protective low voltage relay (LVC); Switch right