


CEE 7/VII

D53 | 12.3% | 87.7% Φ : 14250 lm
 UGR 4H 8H: <10 / <10



| | |
|---------------------------------------|--|
| Light source | LED |
| Work equipment | Electronic ballast |
| Connected load | 220 - 240 V; AC; 50 Hz; 60 Hz |
| Power consumption | ca. 100 W |
| Power factor | env. 0,965 |
| Luminous flux | approx. 14.250 lm |
| Luminous efficiency | approx. 142 lm/W |
| Light type/-color | direct static white; indirectly dynamic white |
| Colour temperatur | approx. 4.000 K; 3.000 - 6.500 K |
| Color rendering index | CRI \geq 80 |
| Light distribution | Direct/indirect |
| Direct ratio | approx. 12 % |
| Glare control | Conical prismatic screen |
| Luminance (L65) | \leq 3.000 cd/m ² |
| Unified glare rating (4H 8H) | \leq 16 |
| System of protection | IP 20 |
| Class of protection | I |
| Technology | Presence and daylight sensor control (PIR); DALI |
| Operation | Multi-function switch |
| Housing | Steel/plastic; Painted; White |
| Light source cover | Acrylic (PMMA); Satine |
| Arm | Steel tube; Painted; Tubular section upright; White |
| Luminaire base | C-form flat |
| Weight (net) | ca. 19,7 kg |
| Mains lead | ca. 3 m; Mains plug; CEE 7/VII |
| Fastening | Floor standing base |
| Decorative contrast side parts | Flint grey |
| Life expectancy LED | L80B50 60.000h |
| Special features | Integrated light and presence sensor PIR; Separated, direct and indirect light individually adjustable; Retrofittable with TALK module; Flicker-free; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; Indirect light component biodynamic light VTL, direct light component neutral working light; Integrated light management for biodynamic light VTL; Luminaire head detachable |