



Light source	LED
Work equipment	Electronic ballast DALI
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 97 W
Power factor	env. 0,959
Luminous flux	approx. 13.800 lm
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Direct ratio	approx. 25 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Conical prismatic screen
Luminance (L65)	≤ 2.700 cd/m ²
Unified glare rating (4H 8H)	≤ 16
System of protection	IP 20
Class of protection	I
Technology	Continuously dimmable; DALI; Touch DIM
Operation	External
Housing	Steel/plastic; Powder coatet; Silver metallic
Light source cover	Polycarbonate (PC); Clear
Weight (net)	ca. 13,4 kg
Mains lead	ca. 1 m; With free stranded wires
Fastening	Steel cable 0.3 - 0.7 m
Configuration	Single Luminaire
Minimum ambient temperature	25 °C
Maximum ambient temperature	25 °C
Decorative contrast side parts	Metallic silver
Special features	Flicker-free; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; DALI Load 2x; Integration into DALI light management systems; Canopy colour (pure white); DALI - dimming via digital rotary dimmer; TouchDIM - dimming via standard switch