


CEE 7/VII



Light source	LED
Work equipment	Electronic ballast
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 63 W
Power factor	env. 0,91
Luminous flux	approx. 8.950 lm
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Direct ratio	approx. 20 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Conical prismatic screen
Luminance (L65)	≤ 3.000 cd/m ²
Unified glare rating (4H 8H)	≤ 16
System of protection	IP 20
Class of protection	I
Technology	Continuously dimmable; DALI
Operation	Multi-function switch
Housing	Steel/plastic; Painted; Silver metallic
Light source cover	Acrylic (PMMA); Satine
Arm	Steel tube; Painted; Tubular section upright; Silver metallic
Weight (net)	ca. 9,5 kg
Mains lead	ca. 3,7 m; Mains plug; CEE 7/VII
Fastening	Socket; Table adaptor
Minimum ambient temperature	25 °C
Maximum ambient temperature	25 °C
Decorative contrast side parts	Metallic silver
Life expectancy LED	L80B50 60.000h
Special features	Separated, direct and indirect light individually adjustable; Flicker-free; Inclination of tubular section adjustable; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; Luminaire head detachable