


CEE 7/VII



**Work equipment**

**Connected load**

**Power consumption**

**Luminous flux**

**Luminous efficiency**

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Direct ratio**

**Chromaticity tolerance LED**

**Glare control**

**Luminance (L65)**

**Unified glare rating (4H 8H)**

**System of protection**

**Class of protection**

**Technology**

**Operation**

**Housing**

**Light source cover**

**Arm**

**Luminaire base**

**Weight (net)**

**Mains lead**

**Fastening**

Electronic ballast

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 79 W

approx. 7.200 lm

approx. 91 lm/W

Cold white

approx. 4.000 K

CRI  $\geq$  90

Direct/indirect

approx. 44 %

< 3 SDCM

See luminaire type

$\leq$  1.600 cd/m<sup>2</sup>

$\leq$  16

IP 20

I

Continuously dimmable; DALI

Pull cord

Polyethylene(PE); Untreated; Anthracite

Polycarbonate (PC); Satine

Steel tube; Painted; Tubular section upright;

Anthracite grey

Round (flat)

ca. 12,3 kg

ca. 2,2 m; Mains plug: CEE 7/VII

Floor standing base