



- Light source** LED
- Work equipment** Adjustable electronic ballast, digital DALI
- Connected load** 220 - 240 V; 50 Hz; 60 Hz
- Power consumption** ca. 47 W
- Lens** W optics, wide beam
- Luminous flux** approx. 8.100 lm
- Luminous efficiency** approx. 172 lm/W
- Light type/color** Cold white
- Colour temperatur** approx. 4.000 K
- Color rendering index** CRI ≥ 80
- Light distribution** Direct
- Direct ratio** approx. 100 %
- Beam angle** 79° / 76°
- Chromaticity tolerance LED** < 3 SDCM
- Glare control** Lens optics
- Luminance (L65)** ≤ 4.400 cd/m<sup>2</sup>
- System of protection** IP 54
- Class of protection** I
- Technology** Continuously dimmable
- Housing** Aluminium; Powder coatet; White
- Light source cover** Acrylic (PMMA); Satine
- Weight (net)** ca. 1,9 kg
- Fastening** Available separately
- Minimum ambient temperature** 0 °C
- Maximum ambient temperature** 42 °C
- Impact strength** IK05
- Life expectancy LED** L80B50 50.000h

LED  
 Adjustable electronic ballast, digital DALI  
 220 - 240 V; 50 Hz; 60 Hz  
 ca. 47 W  
 W optics, wide beam  
 approx. 8.100 lm  
 approx. 172 lm/W  
 Cold white  
 approx. 4.000 K  
 CRI ≥ 80  
 Direct  
 approx. 100 %  
 79° / 76°  
 < 3 SDCM  
 Lens optics  
 ≤ 4.400 cd/m<sup>2</sup>  
 IP 54  
 I  
 Continuously dimmable  
 Aluminium; Powder coatet; White  
 Acrylic (PMMA); Satine  
 ca. 1,9 kg  
 Available separately  
 0 °C  
 42 °C  
 IK05  
 L80B50 50.000h

